

water passageway in the fitting, the second type (40) designed to discharge grey water into the grey water passageway (20a) of the fitting, and the third type, (50, 60) designed to vent to atmosphere both passageways (20a, 20b) in the fitting. A fourth T-fitting (70) is designed to divert reusable grey water into a storage tank and channel sewer water into a sewer system.

PN : EP 0632873 A1 950111  
AN : EP 93908502 930323  
PR : US 855076 920323  
NO : WO 9319320  
DS : DE ES FR GB IT  
MC : F16L- 39/00  
ET : WATER CONSERVING WASTEWATER DISPOSAL SYSTEM  
PT : SYSTEME D'EVACUATION D'EAUX USEES PERMETTANT D'ECONOMISER L'EAU  
GT : ABWASSERBESEITIGUNGSSYSTEM ZUR WASSERERHALTUNG  
PA : DELLE CAVE, Steven F.  
IN : DELLE CAVE, Steven F.  
ND : ESPACE 95/003  
FIRST 93/005 WORLD 93/046

1995

S 1

PN : EP 0632873 A1 950111  
AN : EP 93908502 930323  
PR : US 855076 920323  
NO : WO 9319320  
DS : DE ES FR GB IT  
MC : F16L- 39/00  
ET : WATER CONSERVING WASTEWATER DISPOSAL SYSTEM  
PT : SYSTEME D'EVACUATION D'EAUX USEES PERMETTANT D'ECONOMISER L'EAU  
GT : ABWASSERBESEITIGUNGSSYSTEM ZUR WASSERERHALTUNG  
PA : DELLE CAVE, Steven F.  
IN : DELLE CAVE, Steven F.  
ND : ESPACE 95/003  
FIRST 93/005 WORLD 93/046

S 1

PN : WO 9405866 A1 940317  
AN : AU 9300450 930903  
PR : AU PL 4490 920903  
DS : AT AU BB BG BR BY CA CH CZ DE DK ES FI GB HU JP KP KR KZ LK LU  
MG MN MW NL NO NZ PL PT RO RU SD SE SK UA US VN AT BE CH DE DK  
ES FR GB GR IE IT LU MC NL PT SE BF BJ CF CG CI CM GA GN ML MR  
NE SN TD TG  
MC : E03C- 01/12  
IC : E03B- 11/00  
ET : APPARATUS AND METHOD FOR WASTE WATER RECYCLING  
PT : APPAREIL ET PROCEDE PERMETTANT DE RECYCLER LES EAUX DE DECHARGE  
PA : HYDROSAVE RECYCLING SYSTEMS PTY LTD  
BISHOP, Ronald, Edward  
DODD, Barrie, Eric  
PARRY, Alan, Charles  
IN : BISHOP, Ronald, Edward  
DODD, Barrie, Eric  
PARRY, Alan, Charles

AB : A method of recycling waste water including collecting and storing grey water in a holding tank assembly (11), providing a make-up water supply (18) to the holding tank assembly (11) for maintaining the water level therein between desired levels delivering water from the holding tank assembly to a water flush toilet (17) for flushing the toilet. Preferably, the method further includes providing the water flush toilet with a flushing cistern (17), providing the holding tank assembly with an overflow to waste (12) selecting the desired levels as a lower level sufficient to refill the cistern and an upper level